

500 SERIES

open | EDGE™

By RemoteLOCK



This Wi-Fi enabled smart lock can be connected directly to the internet without a hub. The 500 series lock is designed for residential use and available as either deadbolt or lever.

Key Features

- ✓ Designed to be easy to install, connect, manage and use.
- ✓ Embedded Wi-Fi for standard connectivity. No gateway or hub required.
- ✓ Remote control and monitoring from anywhere using your smartphone or laptop.
- ✓ Supports passage mode, auto-lock mode and passage schedules.
- ✓ Lock retains all programming and data even in the event of power outage or internet interruption.
- ✓ Secure bi-directional encryption. Low battery warning indicator.
- ✓ Store up to 40 weekly access schedules (e.g., M-F, 9-5).
- ✓ Set notifications for user entry and alerts for unexpected issues.
- ✓ Lockout functionality after 5 incorrect code attempts.
- ✓ Utilize temporary codes for guests and visitor management.
- ✓ 2 override keys included.
- ✓ Works with RemoteLock ACS wired solutions.

open|EDGE™ 550DB



What's in the box?

- ✓ Interior and Exterior Lock
- ✓ Deadbolt Latch
- ✓ Strike Plate
- ✓ 2 Physical Override Keys
- ✓ Mounting Plate
- ✓ Mounting Hardware

Deadbolt Specifications

Environment:	For normal internal and external use
Exterior Dimensions:	5½ (H) x 3⅛ (W) x 1½ (D) in.
Interior Dimensions:	7½ (H) x 2⅞ (W) x 2¾ (D) in.
Backset:	2⅝ in. (60mm) or 2¾ in. (70mm)
Locking Device:	Adjustable tubular deadbolt
Construction:	Zinc alloy, suitable for indoor & outdoor use
Operating Temperature:	-31°F (-35°C) to 151°F (66°C)
Thickness:	1⅝ - 2 in. (35mm - 50mm)
Door Handing:	Non-handed, field reversible
Keypad:	10-digit lighted keypad
Batteries:	4 AA (not included)
Keyway:	KW1 5-pin keyway
Code Length:	4 - 10 digits
Code Capacity:	Up to 3,500
Communication:	Single band 2.4GHz Wi-Fi (IEEE 802.11b/g/n) with WPA/WPA2

open|EDGE™ 550L



What's in the box?

- ✓ Interior and Exterior Lock
- ✓ 2 Lever Handles
- ✓ Spring Latch and Strike Plate
- ✓ 2 Physical Override Keys
- ✓ Mounting Plate
- ✓ Mounting Hardware

Lever Specifications

Environment:	For normal internal and external use
Exterior Dimensions:	5½ (H) x 3⅛ (W) x 2½ (D) in.
Interior Dimensions:	7½ (H) x 2⅞ (W) x 3⅜ (D) in.
Backset:	2⅜ in. (60mm) or 2¾ in. (70mm)
Locking Device:	Adjustable tubular latch
Construction:	Zinc alloy, suitable for indoor & outdoor use
Operating Temperature:	-31°F (-35°C) to 151°F (66°C)
Thickness:	1⅞ - 2 in. (35mm - 50mm)
Door Handing:	Non-handed, field reversible
Keypad:	10-digit lighted keypad
Batteries:	4 AA (not included)
Keyway:	KW1 5-pin keyway
Code Length:	4 - 10 digits
Code Capacity:	Up to 3,500
Communication:	Single band 2.4GHz Wi-Fi (IEEE 802.11b/g/n) with WPA/WPA2